



Schottky Barrier Diode



BAS70WTS




BAS70WT-04S



BAS70WT-05S



BAS70WT-06S



Features

- Moisture sensitivity level 1
- Reverse voltage: 70V
- Average forward current : 70mA

Application

- Signal switching
- High frequency rectifier

Mechanical data

- **Package:** SOT-323S
- **Terminals:** Tin plated leads, solderable per J-STD-002 and JESD22-B102

■ Maximum Ratings (T_a=25°C Unless otherwise specified)

Parameter	Symbol	Unit	Value	
Device marking code			BAS70WTS	K73
			BAS70WT-04S	K74
			BAS70WT-05S	K75
			BAS70WT-06S	K76
Repetitive peak reverse voltage	V _{RRM}	V	70	
Forward current	I _F	mA	70	
Non-repetitive surge peak forward current @ t=8.3ms half-sine wave	I _{FSM}	A	0.1	
Non-repetitive surge peak forward current @ t=1ms square wave			2	
Power dissipation	P _D	mW	200	
Junction temperature	T _J	°C	-55 to +125	
Storage temperature	T _{STG}	°C	-55 to +125	



BAS70WTS THRU BAS70WT-06S

RoHS
COMPLIANT

■ Electrical Characteristics (T_a=25°C Unless otherwise specified)

Parameter	Symbol	UNIT	Conditions	Min	Typ	Max
Reverse voltage	V _R	V	I _R =10uA	70		
Forward voltage	V _{F1}	V	I _{FM} =1mA			0.41
	V _{F2}	V	I _{FM} =15mA			1
Reverse leakage current	I _R	uA	V _R =50V			0.2
Junction capacitance	C _j	pF	V _R =1.0V, f=1MHz			2
Reverse recovery time	T _{rr}	ns	I _F =I _R =10mA, I _{rr} =0.1*I _R ,			5

■ Thermal Characteristics

Parameter	Symbol	Unit	Value
Thermal resistance, junction-to-ambient	R _{θJ-A} ⁽¹⁾	°C/W	500
Thermal resistance, junction-to-case	R _{θJ-C} ⁽¹⁾	°C/W	400

Note:

(1) Device mounted on PCB, single-sided copper, with standard footprint



■ Characteristics

Fig 1: P_D - T_a Curve




Fig 2: Capacitance Capability




Fig 3: Typical Forward Characteristics





Fig 4: Typical Reverse Characteristics






BAS70WTS THRU BAS70WT-06S

RoHS
COMPLIANT


■ Ordering Information

Preferred P/N	Packing code	Unit weight(g)	Minimum package(pcs)	Inner box quantity(pcs)	Outer carton quantity (pcs)	Delivery mode
BAS70WTS THRU BAS70WT-06S	F2	Approximate 0.005	3000	30000	120000	7" reel


■ Outline Dimensions



TOP VIEW




SIDE VIEW



SIDE VIEW

DIMENSIONS				
SYMBOL	INCHES		MILLIMETER	
	MIN.	MAX.	MIN.	MAX.
A	0.035	0.043	0.900	1.100
A1	0.000	0.004	0.000	0.100
A2	0.035	0.039	0.900	1.000
b	0.006	0.016	0.150	0.400
c	0.004	0.010	0.100	0.250
D	0.071	0.087	1.800	2.200
E	0.045	0.053	1.150	1.350
E1	0.080	0.096	2.000	2.200
e	0.026 TYP		0.650 TYP	
e1	0.047	0.055	1.200	1.400
L	0.021 REF		0.525 REF	
L1	0.010	0.018	0.260	0.460
θ	0°	8°	0°	8°

■ Suggested Pad Layout





BAS70WTS THRU BAS70WT-06S

RoHS
COMPLIANT

Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function, or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website [http:// www.21yangjie.com](http://www.21yangjie.com) , or consult your nearest Yangjie's sales office for further assistance.